

IMARK

PRODUCT DESCRIPTION



DC2412-10
DC-DC CONVERTER
 24 Volts DC to 13.8 Volts DC, 10 Amps
 Imark Stock # [601410](#)

Features:

- Switch-Mode for Efficiency
- Compact size
- Sealed against the ingress of dirt and moisture
- Continuous duty rated
- Indicators for "Input OK" and "Output OK"
- Remote ON/OFF facility
- Over Temperature Protection
- Over Voltage Protection
- Over Current Protection
- EMI approval

DESCRIPTION:

The Imark DC2412-12 DC-DC Converter is a full specification, compact, ruggedly built unit designed to operate reliably at full 10 Amps load in arduous mining, transport, industrial, agricultural, marine, electrical, and military environments. In-built protection features protect the unit from user tampering often encountered in harsh remote locations.

The compact size allows easy installation in restricted spaces while the unique mounting bracket permits slight bending of the mounting tabs for installation on uneven surfaces. The contoured shape and full sealing against the ingress of dust and moisture allows the unit to be mounted at exposed locations. The DC2412-12 is supplied with a heavy-duty one metre fly lead and mounting screws.

SPECIFICATIONS:	
Input Voltage	20 - 30 Volts DC
Rated Output Current (100% Duty)	10 Amps
Current Limit Setting (@25°C)	11 Amps
No Load Idle Current	35mA
Conducted Emissions	-85dBm
Remote "ON/OFF" Control	Yes
Over Temperature Protection	Yes (@ 85°C)
Over Voltage Protection	Yes (@ 18 Volts)
Over Current Protection	Yes (Foldback)
Output Short Circuit Protection	Yes
Input Reverse Voltage Protection	Yes
User Replaceable Input Fuse	Yes
Isolated Electronics	Yes
Weather Resistant Construction	Yes
Operating Temperature Range	0° to 50° Celsius
Dimensions	85 x 170 x 49 mm
Shipping Dimensions	230 x 190 x 60 mm
Weight	850 grams
Shipping Weight	1 Kg
Inclusions	Operators Manual, Mounting Screws x 4
Approvals	AS/NZS 2064 - 1997, EN55011 - 1991, CISPR 11 - 1997.
Imark Stock #	601410