IMARK PRODUCT DESCRIPTION



DC4212-20 DC-DC CONVERTER

42 Volts DC to 13.8 Volts DC, 20 Amps Imark Stock # 601421

Features:

- Switch-Mode for Efficiency
- Compact size
- Sealed against the ingress of dirt and moisture
- Continuous duty rated
- Indicators for "Input OK" and "Output OK"
- Remote ON/OFF facility
- Over Temperature Protection
- Over Voltage Protection
- Over Current Protection
- Reverse Polarity Protection

DESCRIPTION:

The Imark DC4212-20 DC-DC Converter is a full specification, compact, ruggedly built unit designed to operate reliably at full 20 Amps load in arduous mining, transport, industrial, agricultural, marine, electrical, and military environments. In-built protection features protect the unit from user tampering often encountered in harsh remote locations.

The compact size allows easy installation in restricted spaces while the unique mounting bracket permits slight bending of the mounting tabs for installation on uneven surfaces. The contoured shape and full sealing against the ingress of dust and moisture allows the unit to be mounted at exposed locations. The DC4212-20 is supplied with a heavy-duty one metre fly lead and mounting screws.

| SPECIFICATIONS: | |
|----------------------------------|---|
| Input Voltage | 35 - 45 Volts DC |
| Rated Output Current (100% Duty) | 20 Amps |
| Current Limit Setting (@25°C) | 21 Amps |
| Stand-by Current | 80mA |
| No Load Idle Current | 140mA |
| Efficiency | >80% |
| Conducted Emissions | -85dBm |
| Remote "ON/OFF" Control | Yes |
| Over Temperature Protection | Yes (@ 85°C) |
| Over Voltage Protection | Yes (@ 18 Volts) |
| Over Current Protection | Yes (Foldback) |
| Output Short Circuit Protection | Yes |
| Reverse Polarity Protection | Yes |
| User Replaceable Input Fuse | Yes |
| Isolated Electronics | Yes |
| Weather Resistant Construction | Yes |
| Operating Temperature Range | 0° to 50° Celsius |
| Dimensions | 126 (W) x 170 (D) x 60 (H) mm (excluding Protrusions) |
| Mounting Plate Dimensions | 126 (W) x 211 (D) mm |
| Shipping Dimensions | 190 x 230 x 75 mm |
| Weight | 1.5 Kg's |
| Shipping Weight | 1.7 Kg |
| Inclusions | Operators Manual, Mounting Screws x 4 |
| Standards | AS/NZS 2064 - 1997, EN55011 - 1991, CISPR 11 - 1997. |
| Imark Stock # | 601421 |